Manufacturer Fype of motor	Bharat Bijlee Ltd.3 phase Induction Motor		Customer BBL Enquiry reference No			
Quantity			Customer P.O.Number			
Application	CUSTOME	R TO FURNISH	W.O. No. / SAP No.			
Tag no.			Output kW / Pole	9.3	/	2P
BBL type Ref.		MD13M2N3	Frame size		MJ132	
Installation detail	ils		Applicable standards (latest edition)			
Area classificatio	n (Safe / Hazardous)	Hazardous area		FLP Moto	rs: IS/IEC 6	60079-
Location: indoor/	· · · · · · · · · · · · · · · · · · ·	Indoor	Dimensions: IS 1231/IS 2223/IS:8223			
Altitude (meters)		1000 or less	Vibrations: IS 12075			
			Noise level: IS 12075			
Hazardous area	details		Supply conditions and permissible variations (grid	sunnly)		
-	n GAS (Zone 1/Zone 2)	ZONE I	Number of phases		Three	
Gas group		IIA, IIB	Voltage (Volts) and permisible variation	415	±10	0⁄
Temp.class		T5	Frequency (Hz) and permissible variation	50	±10	
rype or Explosio	n protection	Ex 'd'		50		/0
(EL D/Type 'e'/Type 'n') Approving authority for hazardous area		If Mine application then DGMS else PESO	Combined variation (absolute sum)		±10%	
Electrical param		·		•		
Starting perform						
Method of startin	0	DOL	Starting current (%FLC)	650		
Load speed (rpm)		CUSTOMER TO FURNISH	Starting torque (%FLT)		240	
Motor GD^2 (kgm ²)		0.098	Pull out torque (%FLT)		290	
Load GD^2 (kgm ²		CUSTOMER TO FURNISH	Locked rotor withstand time (hot/cold) (sec)	8	/	16
			Number of consecutive starts (hot/cold) (nos.)			
Load torque-spee		Parabolic TS curve PLEASE FURNISH ALL ABOV	provided Load GD2 = Motor GD2		2/3	
Starting time at ra	ated voltage (sec)	DETAILS				
Running Perform	nance				•	~ 4 \
Efficiency class		-	Duty and designation	Continuous (S1)		<u>SI)</u>
Ambient temp./te	mp.rise by resistance (deg.C)	45 / 75	CDF/Equivalent starts per hour/FI		-	
Enclosure		TEFC (TOTALLY ENCLOSED FAN COOLED)	Insulation class / utilisation class on DOL	F/B		
Full load current	(FLC) amps.	16.5	Rotor type (Squirrel Cage/ Slip ring)	Squirrel Cage		
Full load speed (r	rpm)	2920	Rotor voltage/rotor current (RV/RA) (Volts/Amps)	Not applicable		le
Full load torque (FLT) kg-m		3.11	Stator/rotor time constant (min)	90/122		
Efficiency in % a	t FL/0.75FL/0.5FL	88.0 86.0 83.0	Power factor at FL/0.75FL/0.5FL	0.89	0.85	0.70
Mechanical para	imeters					
Mounting		B8	Mounting dimensions	Re	fer GA drav	ving
Shaft extention		Single cylindrical	Direction of rotation viewed from DE	Clockwise		•
Degree of protect	tion	IP 55	Suitable for bidirectional rotation	Yes		
	g (TEFC/forced cooled/TESC)	TEFC (IC 411)	Paint type	Acid Alkali Proof		oof
Net weight of mo	otor (kg)	120	Paint shade	632 as per IS 5		5
			Earthing provision (two terminals on stator body)		Yes	
Bearings			Terminal box			
Coupling (Direct/	flexible/Belt &	Direct	Terminal box location when viewed from DE	Δα	per GA drav	vino
Pulley/Gearbox)				As per GA drawing		
Dimenssions of p	oulley (OD x width) mm	-	Direction of cable entry	As per GA drawing		
Bearings (roller/b	all/angular contact)	Ball /Ball	Cable size and type(Aluminium)	1R X 3C X 16 SQ MM		
Bearing size DE/NDE		6208 2Z C3/6208 2Z C3	Earthing provision (one terminal in TB)	Yes		
Type of lubrication	on	LITHIUM SOAP BASE GREAS	E tomainala	3	/ DELTA /	6
Accessories		1				
RTDs - 3 number	rs simplex(w/o controller)		Arrow plate for direction of rotation			
BTDs - 1 number per bearing(w/o controller)			Double compression glands (main cable)			
Space heaters - si	ingle phase 50z, 230V		Double compression glands (Space heater/Thermisters/RTDs)			
Thermisters - PT	С		Brake (Type/voltage/torque)			
Additional T-Box	x for Accessories					
Additional namep	olate					
1				-		

2) Performance values are at rated voltage and rated frequency condition and for DOL starting condition.

3) Motor $GD^2 = Load GD^2$ assumed wherever not mentioned.

4) Where starting time is more than 10 seconds, provision of heavy duty relays is mandatory.

5) Kilowatt rating is mandatory and HP is approximate.

6) Accessories provided are marked as "YES"

Prepared by	
Approved by	

			Revison	
Project:	Contractor/Client		Date:	
Consultant	Package			